

Standard Equipment

- ✓ Single-phase 230V/50Hz electric motor
- ✓ Gearmotor with steel and technopolymer gears
- Electric safety: built to EN 60204-1 double insulation norms,
- ✓ protected against spraying water (IP 55) and against overload and inadvertent starting again after a power failure.
- ✓ Packing: cardboard
- ✓ Available in the versions with steel drum and poly drum HDPE (only Rollbeta)

Optional Accessory

- ✓ Rotating pivoting support (only Rollbeta)



115V/60Hz SPH **220V/60Hz SPH**
MOTOR AVAILABLE
 ✓ Rollbeta ✓ Riobeta 140

Rollbeta Applications

It is the lightweight, compact concrete mixer easy to transport, ideal for small building sites or refurbishment work. Its construction features make it suitable for professional use.

Riobeta 140 Applications

Concrete mixer of reduced volume and high discharge. It allows to unload the material directly to the wheelbarrow (without the necessity to use the trestle). Easy access to the drum during the material loading. Easy to use in narrow spaces, with possibility of transport to the floor. Oversized solid wheels ensure the stability on any construction site.

**ROLLBETA
 RIOBETA 140**
 with **STANDARD DOUBLE
 INSULATION** ☐



Rollbeta



Riobeta 140



Rollbeta with poly drum (HDPE)



Rollbeta rotating pivoting support (optional)

		ROLLBETA	RIOBETA 140
Drum capacity	l	134	134
Batch output	l	~100	~100
Drum diameter	mm	610	610
Wheel dimensions	Ø mm	370x60	370x60
Motor power rate	kW	0.3	0.3
Running current	A	2.3	2.8
SPL in operator's position	dB(A)	63	63
Machine weight	kg	46	52
Machine dim. w/l/h	mm	660/1170/920	653/1489/1217
Packing dim. w/l/h	mm	660/730/700	1070/720/660