

MXD8000ME



MXD10000ME



Model	MXD8000ME	
Voltage (V)	110~240	
Frequency (Hz)	50/60	
Max. AC output (kVA)	8KVA	
DC output (V)	12	
Engine model	MX186	
Fuel tank capacity (L)	12.5	
Fuel consumption (L/Hr)	2.76	
Noise(7meter away) dB(A)	≤82	
Dimension (LxWxH) mm	740x475x590	
Net weight (recoil) (kg)	99	
Battery Capacity (Amp)	36 AH	

80 W		5
24 W		5
400 W		1
300 W		1
1Hp		1
1600W (1.0 T)		1

Model	MXD10000ME	
Voltage (V)	110~240	
Frequency (Hz)	50/60	
Max. AC output (kVA)	10kVA	
DC output (V)	12	
Engine model	MX190	
Fuel tank capacity (L)	12.5	
Fuel consumption (L/Hr)	2.76	
Noise(7meter away) dB(A)	≤82	
Dimension (LxWxH) mm	740x475x590	
Net weight (recoil) (kg)	102	
Battery Capacity (Amp)	36 AH	

80 W		10
24 W		10
400 W		1
300 W		2
1Hp		2
3000 W (1.5 T)		1



MODEL: NO	PRIME POWER (KVA/KW)	STANDBY POWER (KVA/KW)	CUMMINS ENGINE DETAIL	ALTERNATOR	CONTROLLER
MG40C1S	(42.5/34)	(40/50)	4DX21-53D	MA234	DSE4620
MG50C1S	(50/40)	(55/44)	1004TG	MA234	DSE4620
MG66CS	(60/48)	(66/53)	1004TG	MA348	DSE4620
MG110CS	(110/88)	(100/80)	6BT5.9-G2	MA480	DSE4510
MG165CS	(150/120)	(165 / 132)	6BTAA5.9-G12	MA4120	DSE4510