

MXT4000LBE (Electric)



Model	MXT3800LBE (Electric)	
Voltage (V)	110~240	
Frequency (Hz)	50/60	
Max. AC output (kVA)	4.0 kVA	
DC output (V)	12	
Engine model	M210	
Displacement (cc)	208	
Engine Speed (rpm)	3000/3600	
Oil Capacity (L)	0.6	
Fuel tank capacity (L)	15	
Continuous operating hour (h)	7.7	
Fuel consumption (L/Hr)	0.98	
Noise(7meter away) dB(A)	≤60	
Dimension (LxWxH) mm	590x433x(430~483)	
Net weight (recoil) (kg)	39	
Noise level dB(A)	67	

80 W		7
24 W		12
400 W		1
300 W		2
1 Hp		1
		

MXT8000LBE (Electric)



Model	MXT8000LBE (Electric)	
Voltage (V)	110~240	
Frequency (Hz)	50/60	
Max. AC output (kVA)	8 kVA	
DC output (V)	12	
Engine model	M420	
Displacement (cc)	420	
Engine Speed (rpm)	3000/3600	
Oil Capacity (L)	1.1	
Fuel tank capacity (L)	25	
Continuous operating hour (h)	6.5	
Fuel consumption (L/Hr)	3.81	
Noise(7meter away) dB(A)	≤75	
Dimension (LxWxH) mm	685x512x550	
Net weight (recoil) (kg)	87	
Noise level dB(A)	75	

80 W		7
24 W		15
400 W		1
300 W		2
1 Hp		1
3000 W (1.5 T)		1

MXT10000LBE (Electric)



Model	MXT10000LBE (Electric)	
Voltage (V)	110~240	
Frequency (Hz)	50/60	
Max. AC output (kVA)	10 kVA	
DC output (V)	12	
Engine model	M460	
Displacement (cc)	460	
Engine Speed (rpm)	3000/3600	
Oil Capacity (L)	1.1	
Fuel tank capacity (L)	25	
Continuous operating hour (h)	5.5	
Fuel consumption (L/Hr)	3.81	
Noise(7meter away) dB(A)	≤76	
Dimension (LxWxH) mm	685x512x550	
Net weight (recoil) (kg)	90	
Noise level dB(A)	76	

80 W		8
24 W		20
400 W		1
300 W		2
1 Hp		1
4000 W (2.0 T)		1

MXT11000LBE (Electric)



Model	MXT11000LBE (Electric)	
Voltage (V)	110~240	
Frequency (Hz)	50/60	
Max. AC output (kVA)	11 kVA	
DC output (V)	12	
Engine model	M460	
Displacement (cc)	460	
Engine Speed (rpm)	3000/3600	
Oil Capacity (L)	1.1	
Fuel tank capacity (L)	25	
Continuous operating hour (h)	4.8	
Fuel consumption (L/Hr)	3.81	
Noise(7meter away) dB(A)	≤76	
Dimension (LxWxH) mm	685x512x550	
Net weight (recoil) (kg)	94	
Noise level dB(A)	76	

80 W		8
24 W		22
400 W		1
300 W		2
1 Hp		1
5000 W (2.5 T)		1