



TYROLIT

CUT OFF MACHINE

STRONG

&

TOUGH

WORKING CAPACITY

Bar Dia.	80 mm
Pipe Dia. (MS/SS)	120 mm
Steel	140x140 mm
Angles	100x100x12 mm
Channels	100x15x12 mm

SPECIFICATIONS

Code	10996457
RPM	3800
Volts (V)	440
Power Input	3700 Watts
Wheel Dia.	400mm/16" & 350mm/14"
Weight	105 kg
Motor	3ph/5 HP A/C

APPLICATION

Ferrous Metals	Abrasive Wheel
----------------	----------------

TYROCUT - MI 400

This amazingly fast machine runs on a 5 HP 3 Phase induction motor with single phase preventer, ball bearing hinges & double belt driven mechanism. Widely used in civil construction and heavy steel fabrication industry.



TYROLIT

A Company of the SWAROVSKI Group

Contact:



WE CARE

MACHINERY

COMMITTED TO QUALITY

Tel : +971 2 575 9585
Fax : +971 2 575 9586

P.O.Box: 132577, Sector M-45
Shop No: 90, Musaffah,
Abu Dhabi, U.A.E.

Mob : +971 58 890 5681

Email: info@wecaregroup.net

www.wecaregroup.net